

Modules for Power Factor Correction Systems

Type C...D



Article-No.	Rated Power in kvar at 400V	Step Power in kvar at 400V	Switching Sequence	Type and order code
Capacitor-Reactor-Module, type: C84D / C85D				
P1: series resonance frequency 134Hz, p = 14%				
34-64069	25.00	6.25	1:1:2	C84D 25-6.25-21-400/480-84-P1
34-64070	25.00	12.50	1:1	C84D 25-12.5-2-400/480-84-P1
34-64039	25.00	25.00	-	C84D 25-25-1-400/480-84-P1
34-64271	31.25	6.25	1:2:2	C84D 31.25-6.25-12-400/480-84-P1
34-64374	37.50	6.25	1:1:2...	C84D 37.5-6.25-22-400/480-84-P1
34-64018	37.50	12.50	1:2	C84D 37.5-12.5-11-400/480-84-P1
34-64002	43.75	6.25	1:2:4	C84D 43.75-6.25-111-400/480-84-P1
34-64003	50.00	12.50	1:1:2	C84D 50-12.5-21-400/480-84-P1
34-64004	50.00	25.00	1:1	C84D 50-25-2-400/480-84-P1
34-64005	50.00	50.00	-	C84D 50-50-1-400/480-84-P1
34-64006	75.00	25.00	1:2	C84D 75-25-11-400/480-84-P1
34-64040	100.00	50.00	1:1	C85D 100-50-2-400/480-85-P1
P7: series resonance frequency 189Hz, p = 7 %				
34-64071	25.00	6.25	1:1:2	C84D 25-6.25-21-400/440-84-P7
34-64072	25.00	12.50	1:1	C84D 25-12.5-2-400/440-84-P7
34-64015	25.00	25.00	-	C84D 25-25-1-400/440-84-P7
34-64339	31.25	6.25	1:2:2	C84D 31.25-6.25-12-400/440-84-P7
34-64073	43.75	6.25	1:2:4	C84D 43.75-6.25-111-400/440-84-P7
34-64305	46.88	3.13	1:2:4:8	C84D 46.88-3.13-1111-400/440-84-P7
34-64007	50.00	6.25	1:1:2:4	C84D 50-6.25-211-400/440-84-P7
34-64008	50.00	12.50	1:1:2	C84D 50-12.5-21-400/440-84-P7
34-64009	50.00	25.00	1:1	C84D 50-25-2-400/440-84-P7
34-64010	50.00	50.00	-	C84D 50-50-1-400/440-84-P7
34-64041	62.50	12.50	1:2:2	C84D 62.5-12.5-12-400/440-84-P7
34-64074	68.75	6.25	1:2:4...	C84D 68.75-6.25-112-400/440-84-P7
34-64848	75.00	12.50	1:2:3	C84D 75-12.5-11A-400/440-84-P7
34-64011	75.00	25.00	1:2	C84D 75-25-11-400/440-84-P7
34-64012	87.50	12.50	1:2:4	C84D 87.5-12.5-111-400/440-84-P7
34-64648	100.00	12.50	1:1:2...	C85D 100-12.5-211-400/440-85-P7
34-64013	100.00	25.00	1:1:2	C84D 100-25-21-400/440-84-P7
34-64014	100.00	50.00	1:1	C84D 100-50-2-400/440-84-P7

Dimensions C84D: WxHxD 700x300x350 mm (for cabinets with a min. W / D: 800 x 400 mm)

Dimensions C85D: WxHxD 700x300x450 mm (for cabinets with a min. W / D: 800 x 500 mm)